

# PORTABLE INDIRECT OIL FIRED HEATERS

Traditional Belly Tank;  
BT.15, BT.20 & BT.25



HeatEasi with remote Fuel Barrel  
or Bulk Fuel Tank;  
HE.20, HE.25, HE.50,  
HE.60Uno & HE.90Uno



HeatEasi with Belly Tank and/or  
separate Fuel Barrel/ Tank;  
HE.15BT, HE.20BT & HE.25BT



## COOLING AND HEATING SOLUTION'S RANGE OF EQUIPMENT:

- \* Air Cooled Heat Pump Chillers
- \* Commercial and Industrial Fan Coils
- \* LPHW Cast Iron Boilers
- \* Plate Heat Exchangers
- \* Water & Condensate Pumps
- \* Indirect Oil Fired Heaters
- \* Portable Air Conditioners
- \* Spot Coolers
- \* Portable Electric Heaters
- \* Fans and Ventilators
- \* Dehumidifiers
- \* Radiant Heaters
- \* dX Split Systems
- \* Air Handlers
- \* Building Dryers
- \* Bunded Fuel Tanks
- \* Road Certified Fuel Tanks
- \* Temperature Monitoring



**COOLING & HEATING SOLUTIONS**  
TEMPERATURE CONTROL SPECIALISTS

Marlwood House  
Silver Street  
Lymington  
Hampshire  
SO41 6DG  
UK

T. +44 (0) 1590 681 434

E. [sales@candhs.co.uk](mailto:sales@candhs.co.uk)

W. [www.coolingandheatingolutions.com](http://www.coolingandheatingolutions.com)



TECHNICAL INFORMATION:

Characteristics	Units	BT.15	BT.20	BT.25	HE.15BT	Model Reference					
						HE.20BT & HE.20	HE.25BT & HE.25	HE.50	HE.60Uno	HE.90Uno	
Heat Output Net	kW/hr	15	20	25	15	20	25	50	60	90	
Heat Output Net	Btu/hr	51180	68240	85300	51180	68240	85300	167188	204,720	307,080	
Air Flow	M <sup>3</sup> /hr	600	1250	1250	600	1250	1250	1900	2800	4800	
Efficiency	%	64	85	82	64	85	82	84	84	85	
Oil Consumption	Litres/hr +/-	1.65	2.2	2.9	1.65	2.2	2.9	5.6	4.84	7.72	
Electrical Supply	V/A/hz	← 230/1/50 or Dual 110/230 →									
Running Current	Amps	0.7	0.7	1.1	0.7	0.7	1.1	1.3	2	4	
Air Outlet Dia	mm	205	250	250	205	250	250	350	315	435	
Body Diameter	mm	245	320	320	245	320	320	420	385	490	
Flex Air Duct Dia	mm	250	320	320	250	320	320	420	395	565	
Chimney Dia	mm	120	120	120	120	120	120	150	150	150	
Weight	kg	36	48	52	36	48	52	103	91	147	
Length	mm	860	1250	1250	860	1250	1250	166	1410	1720	
Width	mm	470	550	550	470	550	550	1700	460	720	
Height	mm	570	810	810	570	810	810	560	960	1060	

Standard sized quick connect Fuel Barrels (non-bunded) are available in 30 and 120 litre formats. Larger Bulk Tanks up to 5000 litres are also available.

Flexible Warm Air Duct



Air Diffuser



Transformer Kit



Tiger Loop



Thermost



Flue and Rain Cap



100L Bunded Fuel Trolley



Weatherproof Cover



Fuel Barrels



COOLING & HEATING SOLUTIONS  
TEMPERATURE CONTROL SPECIALISTS

Marlwood House  
Silver Street  
Lymington  
Hampshire  
SO41 6DG  
UK

T. +44 (0) 1590 681 434  
E. sales@candhs.co.uk

W. [www.coolingandheatingsolutions.com](http://www.coolingandheatingsolutions.com)

